

BAFFLE PLATES

337-365-4411

sales@k-e-t.com

**BAFFLE
PLATES**

Baffle plates can be placed on top of the drill-pipe float valve or the drill bit too help prevent damage from recorders or other wire-line tools that are dropped down the string.

**BAFFLE PLATES
RING AND SPIDER TYPE**



RING TYPE



SPIDER TYPE

| PART NO. | CONNECTION TYPE/SIZE | DPFV SIZE | TYPE | WEIGHT (lbs) | BAFFLE PLATE OD |
|-------------|----------------------|-----------|--------|--------------|-----------------|
| K-91701 ** | 2-7/8"API REG | 1F-2R | SPIDER | 0.5 | 1.94 |
| K-91702 ** | 3-1/2"API REG | 2F-3R | RING | 0.4 | 2.28 |
| K-91703 ** | 4-1/2"API REG | 4R | RING | 0.8 | 3.22 |
| K-91704 ** | 5-9/16"API REG | 5R | RING | 1.3 | 3.87 |
| K-91705 ** | 6-5/8"API REG | 5F-6R | RING | 1.5 | 4.63 |
| K-91706 ** | 7-5/8"API REG | 5F-6R | RING | 1.7 | 5.33 |
| K-91707 ** | 8-5/8"API REG | 6F | RING | 2.2 | 6.18 |
| K-91711 *** | REPLACED BY K-91721 | 3F | SPIDER | 0.6 | 2.75 |
| K-91712 *** | 4-1/2"API FH | 4F | RING | 0.9 | 3.36 |
| K-91713 *** | 5-9/16"API FH | 5F-6R | RING | 1.5 | 4.63 |
| K-91714 ** | 6-5/8"API FH | 6F | RING | 2.2 | 5.45 |
| K-91721 * | 3-1/2"API FH | 3F | SPIDER | 0.6 | 2.63 |
| K-91722* | 4-1/2" API FH | 4F | SPIDER | 0.7 | 3.44 |
| | 4-1/2" API REG | 4R | | | |
| | 5-9/16" API REG | 5R | | | |
| K-91723* | 5-9/16" FH | 5F-6R | SPIDER | 1.0 | 4.68 |
| | 6-5/8" FH | 5F-6R | | | |
| K-91724 * | 6-5/8"API FH | 6F | SPIDER | 1.0 | 6.56 |
| K-91725 * | 3-1/2"API IF | 3.5IF | SPIDER | 0.6 | 3.06 |
| K-91726 * | REPLACED BY K-91722 | 5R | SPIDER | 0.8 | 3.76 |
| K-91741 *** | 3-1/2"API IF | 3.5IF | RING | 0.7 | 3.06 |
| K-91742 *** | 4-1/2"API IF | 5R | RING | 1.6 | 4.22 |
| K-91743 *** | 2-7/8"API IF | 2F-3R | SPIDER | 0.7 | 2.44 |
| K-91744 *** | 4"API IF / 4-1/2"XH | 4F | RING | 1.0 | 3.88 |

* For use on float. **For use on bit. ***For use in joint.