

BIT SUB INFORMATION

337-365-4411

sales@k-e-t.com

VALVE SIZE	THREAD SIZE	TOOL JOINT TYPE	STANDARD OD	FACE TO SHOULDER OR FACE TO FACE	
1R	2-3/8"	API REGULAR	3-1/8"	18"	
1F-2R	2-7/8"		3-3/4"	20"	
2F-3R	3-1/2"		4-1/4"	20"	
4R	4-1/2"		5-1/2"	24"	
5R	5-1/2"		6-3/4"	28"	
5F-6R	6-5/8"		7-3/4"	30"	
5F-6R	7-5/8"		8-7/8"	30"	
6F	8-5/8"		10"	30"	
3F	3-1/2"		API FULL HOLE	4-5/8"	24"
3.5 IF	4"			5-1/4"	24"
4F	4-1/2"	5-3/4"		28"	
5F-6R	5-1/2"	7"		30"	
6F	6-5/8"	8"		30"	
1F-2R	2-3/8"	API IF	3-3/8"	18"	
2F-3R	2-7/8"	API IF BOX X PIN	4-1/8"	20"	
3.5 IF	3-1/2"	API IF	4-3/4"	24"	
4F	4"		5-3/4"	28"	
5R	4-1/2"		6-3/8"	28"	
5F-6R	5-1/2"		7-3/8"	30"	
6F	6-5/8"		8-3/4"	30"	

The information guide above is for reference purposes only. Please use appropriate API specifications when manufacturing these subs.